

Overview and selection chart

	SPE HG	SPE VOL	SPE ppm	SPE OD	SPE DUO
Recommended for the following current devices	SNOOPER 4 PM 4 GM 4 SNOOPER mini	SR2-BIO HS 6xx Multitec 5XX VARIOTEC 4XX VARIOTEC 460 Tracergas	PORTAFID HS 660 / HS 680 VARIOTEC 4XX VARIOTEC 460 Tracergas	OD 4	HS 660 / HS 680 VARIOTEC 4XX
In general for devices that can be tested	Handheld devices and diffusion devices with a pump capacity of ≤ 20 l/h	Pump devices with a pump capacity of > 20 l/h	FID devices and devices with semiconductor sensors with a pump capacity of > 20 l/h	Odor measuring devices	Combination measuring devices with semiconductor sensors with a pump capacity of > 20 l/h
Gas release	Key	Key	Key	Switch	Key
Flowmeter with needle valve	no	yes	yes	no	yes
Manometer	yes	yes	yes	yes	yes - two
Conditioner	no	no	yes	no	yes - one
Device connection	Plug-in connection 5 mm	Plug-in connection 5 mm	Plug-in connection 5 mm	Safe-lock connection 3 mm	Plug-in connection 5 mm
Gas flow	approx. 30 l/h, fixed	0 – 80 l/h, adjustable	0 – 80 l/h, adjustable	approx. 30 l/h, fixed	0 – 80 l/h, adjustable
Part no.	PP01-10201	PP01-90101	PP01-40101	PP01-50100	PP01-60001